



ENGINEERED TO PERFORM. BUILT TO LAST.

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

F12

LIGHT DUTY TWO POST LIFT 12,000 lbs. Capacity



INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"



FWD F12N300BL

FEATURES:

Symmetrical column design

2-stage front and rear arms

Four height configuration models for most ceiling heights

Adjustable width options

- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed inside carriage
- Overhead cable equalization
- Single point lock release
- Powder coated finish
- Includes adapter storage bracket
- ALI Certified

Forward Lifts meet the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.



SPECIFICATIONS	F12N300BL/RD*
Capacity	12,000 lbs. (5443kg)
Maximum Rise	77-1/2" (1968mm) w/5" extension
Adjustable Overall Height Options	F12N300 166" (4216mm) Standard
	F12N301 178" (4521mm) Max. Height
	F12N302 154" (3912mm)
	F12N303 143" (3632mm)
Overall Width	140" (3556mm) or optional 146" (3708mm)
Drive through clearance	108-3/4" (2762mm) or optional 102-3/4" (2610mm)
Overhead switch height Options	F12N300 160-1/8" (4067mm) Standard
	F12N301 172-1/8" (4524mm) Extended
	F12N302 148-1/8" (3762mm)
	F12N303 137-1/8" (3483mm)
Front reach (Min/Max)	35" / 54" (889mm/1372mm)
Rear reach (Min/Max)	35" / 54" (889mm/1372mm)
Adapter Height	Min/Max 4-3/4" (121mm) w/o extension
	9-3/4" (248mm) w/5" extension
	Width Inside Columns 120-7/8" (3070mm) Adjustable
	114-7/8" (2918mm) Standard
Voltage/Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP/50Hz; 1ph/2HP/60Hz
Ceiling Height Required	168" (4267mm)



996 Industrial Drive
Madison, IN 47250

Phone: 800.423.1722
Fax: 812.273.7329



www.forwardlift.com



Lit# Forward F12 CUTSHEET.2019.10 ©2019 Vehicle Service GroupSM All rights reserved.

Unless otherwise indicated, Forward Lift, Vehicle Service GroupSM, Dover and all other trademarks are property of Dover Corporation and its affiliates. Printed in the U.S.A.

*Lifts available in blue and red
Specifications subject to change without notice or liability.