HOLLSTEIN

PERFORMANCE TIRE CHANGERS

SWING ARM DESIGN -HANDLES TIRES TO 47" DIAMETER AND RIM WIDTHS TO 15".

This model has power to spare and a 26" x 26" square turntable that can handle wheel diameters up to 47" with ease.

SPECIFICATIONS:

Max wheel diameter 47"

Max wheel width 3"-15"

Rim diameter inside 15"-28"

Rim diameter outside 13"-24"

Working pressure 10 bar

Power supply 1½ hp 110 vac

Bead breaker 5500 lb



High performance Automatic Tire changer with press arm

Features:

- · Swing arm design
- Handles tires to 47"
 and rim widths to 15"
- Four pneumatic clamps and double acting cylinders
- Side mounted bead breaker
- Press arm for low profile tires
- Bead seating inflation jets in clamping jaws
- No scratching.
 Machine never contacts rim
- Lubricator, separator and air pressure regulator

Features:

- Large square turn table
- Tilting column and pneumatic locking system
- Bead seating inflation jets are integrated in the clamping jaws for quick and safe inflation
- Twin clamping cylinders provide more power to hold the most difficult rims
- Conveniently located powerful bead breaker

- No scratching machine never contacts rim
- Large diameter hex mount /demount shaft for extra rigidity
- Pressure regulator, oiler and water separator standard
- Assist arm for changing stiff low-profile tires.
 All the bell and whistles to take the work out of low profile tire repairs

SPECIFICATIONS:			
SPECIFICATIONS:			
OFECIFICATIONS.			

External clamping	13"-24"	
Internal clamping	15"-28"	
Max wheel diameter	47 ½"	
Wheel width	3"- 15"	
Bead breaker	5500 lb	
Operating pressure	110 - 147 psi	

1082 School House Rd, Harveys Lake, Pa 18618 570 639 2344 aetechnologiesinc.com